



Product Data

Castrol Braycote 236

Coolant Fluid, Hydrolytically Stable
Dielectric

Description

Castrol Braycote™ 236 is a soft, reddish-brown grease-like technical grade petrolatum. It forms a soft, translucent, flexible coating on parts to which it is applied, and is readily removed with solvent or by steam cleaning processes.

Application

Braycote 236 is intended for use as a light grade of lubricating grease, but is not recommended for use in heavily loaded or hot running bearings. It may be used as a constituent in petrolatum base rust preventive compounds.

Specification

Braycote 236 meets the requirements of Federal Specification VV-P-236A.

Typical Characteristics

TEST METHOD	DESCRIPTION	VV-P-236A REQUIREMENTS	RESULT
D 1500	Color, ASTM	2-8	<3.0
D 127	Melting Point, °F (°C)	115-140 (46-60)	133 (56)
D 92	Flash Point, COC, °F (°C)	390 (198) Minimum	480 (248)
D 937	Penetration, Unworked, mm/10	150 - 275	194
FTM 5309	Corrosion on Copper, 24 hours, 100 °C (212 °F)	None	None
D 482	Ash Content, %	0.1 Maximum	0.01
D 974	Neutralization Number, mg KOH/g	0.1 Maximum	0.014
D 91	Precipitation Number	0.10 Maximum	0.005
Spec	Abrasive Material	None	None
Spec	Evaporation Loss 1 hour, 107 °C (225 °F), % wt	2 Maximum	0.10
D 97	Pour Point, °F (°C)	Report	130 (54)
D 445	Viscosity @ 100 °C (212 °F), cSt	11.6-18.0	13

Subject to usual manufacturing tolerances.

Castrol Braycote 236
8/14/2008, version 5.0
Castrol, Brayco and the Castrol logo are trademarks of Castrol Limited, used under licence.

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Industrial North America Inc. 150 West Warrenville Road, 605 3E Naperville, IL 60563
Tel: (877) 641 1600 Fax: (877) 648 9801
www.castrol.com/industrial