



Product Data

Castrol Brayco® 815Z

Wide Temperature Range
Perfluorinated Polyether Lubricating Oil

Description

Castrol Brayco 815Z is a clear water white perfluorinated polyether based fluid. It is virtually inert, compatible with rocket propellants and oxidizers, is unaffected by ultraviolet, cosmic radiation, or high vacuums. It has an exceptionally high viscosity index and low volatility, and has little tendency to form deposits. This product is highly recommended for use in applications at low temperature extremes and in high vacuum. It exhibits excellent lubricating properties, good dielectric properties, excellent shear stability, and low toxicity. Castrol Fluoroclean™ X100 or Castrol Fluoroclean™ HE can be used to remove this lubricant. Refer to the data sheets for information regarding these products.

Application

Brayco 815Z is essentially insoluble in current fuels and oxidizers, as well as in most organic solvents. This product is intended for use in extreme environments, and has been used successfully in many space missions and in sensitive electronic equipment. It is particularly suited for those applications where extreme vacuums and wide temperature variations are common. Perfluorinated fluids, in general, exhibit excellent shelf lives due to their intrinsic inertness.

Characteristics

TEST METHOD	DESCRIPTION	RESULT
D 287	Specific Gravity @ 16/16°C (60/60°F)	1.8531
	Pounds per Gallon @ 16°C (60°F)	15.430
D 445	Kinematic Viscosity, cSt	
	@ 99°C (210°F)	45
	@ 38°C (100°F)	148
	@ -40°C (-40°F)	6,500
	@ -54°C (-65°F)	10,855
D 2270	Viscosity Index	350
D 97	Pour Point, °C (°F)	-72 (-100)
BOC	Evaporation Loss, % wt 72 hrs, 232°C (450°F)	0.36
D 664	Acid Number, mgKOH/g (end point, pH=8.2)	0.01
Knudsen	Vapor Pressure, torr	
	@ 20°C (68°F)	4×10^{-13}
	@ 100°C (212°F)	2×10^{-9}
E 595	Vacuum Stability Test	
NASA	Total Weight Loss, % wt	0.081
SP-R-0022A	Volatile Condensable Material, % wt	0.012
FTM 3009	Solid Particle Contamination	
	Number of Particles per 100 mL	
	5 - 15 microns	163
	16 - 25 microns	42
	26 - 50 microns	16
	51 - 100 microns	4
	+ 100 microns	Nil

Health, safety and environmental information are provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products. Castrol will not accept liability if the product is used other than in the manner or with the precautions or for the purpose(s) specified. Before using the product other than directed, please contact Castrol for consultation.

Additional Information

Temperature Range

-72°C to above 204°C (-100°F to 400°F) under normal operating conditions and up to 260°C (500°F) for brief periods.

Limitations

Brayco 815Z is compatible with all commonly utilized materials, plastics, and elastomers. It may be adversely affected by Lewis Acid Catalysts such as aluminum chloride at elevated temperatures. Newly exposed rubbing surfaces of aluminum, magnesium, or titanium alloys may react with this product under certain conditions. Such systems should be thoroughly evaluated. Surfaces must be well cleaned of organic rust inhibitors prior to oil application to ensure proper lubrication.

Packaging

Brayco 815Z is packaged in 2 ounce (AVDP) bottles and in 1 pound jars. A specially prepared "Micronic" grade - ultra filtered - is available on request.

Castrol Brayco 815Z
07.15.2005, Version Number 2.0
Brayco 815Z and the Castrol logo are trademarks of Castrol Limited.

All reasonable care has been taken to ensure that the information contained in this publication is accurate as of the date of printing. However, such information may, nevertheless, be affected by changes in the blend formulation occurring subsequent to the date of printing. Material Safety Data Sheets are available for all Castrol Ltd products. The MSDS must be consulted for appropriate information regarding storage, safe handling and disposal of a product.

Castrol Industrial North America Inc. 150 West Warrenville Road, 605 3E Naperville, IL 60563
Tel: (877) 641 1600 Fax: (877) 648 9801

www.castrol.com/industrial