



Heat Transfer Oil

Conoco Heat Transfer Oil is a high-quality, thermally stable, inhibited mineral oil developed for use in both open and closed liquid-phase heat transfer systems.

Heat Transfer Oil is available in one viscosity grade: ISO 32. It is formulated with high-quality, hydroprocessed paraffinic base oils that have good thermal stability and low sludge-forming tendency. It is fortified with select additives that provide enhanced oxidation resistance for long service life, and detergency to help keep the system clean for maximum heat transfer efficiency.

Applications

Heat Transfer Oil is recommended for use in closed liquid-phase heat transfer systems equipped with expansion tanks and pressure relief valves, where the maximum bulk oil temperature does not exceed 550°F (288°C). Preventive measures should be taken to minimize oil oxidation by eliminating air from the system prior to bringing the oil up to operating temperature. The use of an inert gas, such as nitrogen, under positive pressure in the expansion tank is recommended at all times during operation. Under no circumstances should the hot oil come into contact with air.

Heat Transfer Oil also is recommended for use in open liquid-phase heat transfer systems equipped with cold-oil sealed expansion tanks, where the maximum bulk oil temperature does not exceed 374°F (190°C).

Heat Transfer Oil is **not** recommended for use in vapor-phase heat transfer systems. Follow the equipment manufacturer's recommendations on oil change intervals, and for recommended practices when switching over from another brand of heat transfer oil.

Some common heat transfer applications for Heat Transfer Oil include:

- Direct and indirect-fired hot oil heaters in asphalt plants
- Hot corrugation and gluing
- Dehydration
- Molding and extrusion equipment
- Plastic and wax coating equipment

**Inhibited
Heat Transfer Oil
For Open And
Closed Systems**

**U.S. Technical
Services Hot Line:
1-800-255-9556**

**U.S. Customer
Service:
1-800-640-1956**

**International:
+1-832-486-3363**

**E-mail address:
*conocolubricants@
conocophillips.com***

www.lubes.conoco.com

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



- Organic synthesis hot oil systems

Features/Benefits

- Excellent resistance to thermal breakdown at high temperatures
- Excellent performance in both open and closed heat transfer systems
- Long service life
- Excellent deposit control
- Low odor
- Noncorrosive

Heat Transfer Oil

Typical Properties

ISO Grade	32
Density, g/cm ³ @ 15.6°C (60°F)	0.856
Density, lbs/gal @ 15.6°C (60°F)	7.13
Color, ASTM D1500	L 1.0
Flash Point (COC), °C (°F)	218 (424)
Autoignition Temperature, ASTM E659, °C (°F)	360 (680)
Pour Point, °C (°F)	-40 (-40)
Viscosity,	
cSt @ 40°C	31.0
cSt @ 100°C	5.4
SUS @ 100°F	160
SUS @ 210°F	44.4
Viscosity Index	108
Carbon Residue, ASTM D524, wt %	0.17
Specific Heat, Btu/lb-°F),	
@ 0°F (-18°C)	0.418
@ 200°F (93°C)	0.515
@ 400°F (204°C)	0.612
@ 550°F (288°C)	0.685
Vapor Pressure @ 260°C (500°F), mm Hg	8.0

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Due to continual product research and development, the information contained herein is subject to change without notification.

Copyright © 2007 ConocoPhillips Company. The ConocoPhillips logo, Conoco, and the Conoco logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.