



## Multipurpose R&O Oil

Multipurpose R&O Oil is a rust and oxidation (R&O)-inhibited, antiwear circulating oil developed for use in circulation systems, centrifugal air compressors, geared turbines, lightly loaded gearboxes and many other industrial applications. It contains a low level of ashless (zinc-free) antiwear additive for mild wear protection.

Multipurpose R&O Oil is formulated to provide protection against rust, corrosion and deposit formation, plus mild wear protection. It has good oxidation resistance at high temperatures to minimize sludge and varnish formation, resulting in long service life. It protects system components against rust and corrosion. It has excellent water-separating properties to minimize the formation of emulsions, and is resistant to excessive foam buildup that can interfere with proper lubrication. An ashless antiwear additive provides mild wear protection to help increase equipment life.

### **Applications**

- Air tools and other pneumatic equipment lubricated through air line lubricators
- Centrifugal air compressors
- Steam turbines and hydroelectric turbines, both direct-drive and with gear drives
- Lightly loaded enclosed industrial gearboxes that do not require a compounded or extreme-pressure (EP) gear oil (ISO VG 68 and higher)
- Lightly loaded plain and rolling-element bearings, such as those in electric motors and blowers
- Vacuum pumps, deep-well water pumps and machine tools
- General-purpose machinery and shop lubrication

Multipurpose R&O Oil meets the requirements of the following industry and OEM specifications:

- ABB G12106
- AGMA Grades 0 through 7 (non-EP)
- Alstom Power HTGD 90 117 for geared turbines
- ASTM D4304 Type I Turbine Oil (ISO VG 32, 46, 68, 100)
- British Standard 489
- Denison Hydraulics HF-1
- DIN 51517 Part 1, Lubricating Oils, Type CL
- DIN 51524 Part 1, Hydraulic Oils, Type HL
- General Electric GEK 101941A, GEK 46506D, GEK 27070 (obsolete), GEK 28143A (obsolete)

**Rust & Oxidation-  
Inhibited, Antiwear  
Circulating Oil**

### **Contact Information**

**U.S. Customer  
Service:  
1-800-822-6457**

**U.S. Technical  
Services Hot Line:  
1-800-766-0050**

**International:  
+1-832-486-3363**

**E-mail address:  
lubricants@  
conocophillips.com**

<http://lubricants.conocophillips.com>

600 N. Dairy Ashford • 2W9000 • Houston, TX 77079



conoco



- Ingersoll-Rand Centak centrifugal compressors
- Solar Turbines ES 9-224 Class II Turbine Oil
- U.S. Military MIL-L-17672D
- U.S. Steel 126

### **Features/Benefits**

- Good oxidation resistance to minimize sludge and varnish formation
- Mild wear protection
- Protects against rust and corrosion
- Excellent water-separating properties
- Low carbon-forming tendency for use in centrifugal air compressors
- Good foam resistance

---

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

---

Copyright © 2008 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.



## Multipurpose R&O Oil

### Typical Properties

ISO Grade	22	32	46	68	100	150	220	320	460
<b>AGMA Grade</b>	—	0	1	2	3	4	5	6	7
Specific Gravity @ 60°F	0.855	0.859	0.863	0.868	0.870	0.879	0.891	0.898	0.895
Density, lbs/gal @ 60°F	7.13	7.16	7.20	7.24	7.25	7.33	7.43	7.49	7.46
Color, ASTM D1500	L 0.5	L 0.5	L 0.5	L 0.5	L 0.5	2.5	3.5	4.5	5.0
Flash Point (COC),									
°C	210	232	238	243	268	277	285	304	307
°F	410	450	460	469	514	531	545	579	585
Pour Point,									
°C	-40	-40	-40	-34	-34	-17	-15	-15	-15
°F	-40	-40	-40	-29	-29	1	5	5	5
Viscosity,									
cSt @ 40°C	22.0	32.5	45.0	68.2	101	158	220	318	464
cSt @ 100°C	4.3	5.4	6.7	8.8	11.3	14.6	18.9	23.9	30.6
SUS @ 100°F	115	168	232	353	527	833	1,164	1,694	2,488
SUS @ 210°F	40.7	44.4	48.7	55.9	65.0	78.1	96.4	119	150
Viscosity Index	100	101	102	100	97	97	97	95	96
Acid Number, ASTM D974, mg KOH/g	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14	0.14
Copper Corrosion, ASTM D130	1a	1a	1a	1a	1a	1a	1a	1a	1a
Demulsibility, ASTM D1401,									
minutes to pass	20	20	20	20	20	20	20	20	25
Foam Test, ASTM D892	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Four-Ball Wear, ASTM D4172,									
Scar Diameter, mm	—	0.54	0.48	0.45	0.45	0.41	0.41	0.40	0.40
FZG Scuffing Test, ASTM D5182,									
Failure Load Stage	—	10	10	10	10	10	10	10	10
Oxidation Stability,									
TOST, ASTM D943-04a, hours	—	4,500	4,500	4,500	4,500	4,000	4,000	4,000	4,000
RPVOT, ASTM D2272, minutes	—	750	750	700	700	700	700	700	700
Rust Test, ASTM D665 A&B	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass	Pass

### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3.conocophillips.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

Copyright © 2008 ConocoPhillips Company. The ConocoPhillips logo, Conoco, the Conoco logo, Phillips 66, the Phillips 66 logo, 76 and the 76 logo are trademarks of ConocoPhillips Company in the U.S.A. and other countries.