



# Santex Chain Oil 400

## PRODUCT INFORMATION

*Santex 400 High Temperature Chain Oil (SCO 400) is a unique formulation of special ester base stocks and the latest additive technology. SCO-400 has an exceptionally high smoke point and is capable of penetrating and removing carbonaceous deposits and inhibiting the formation of solid buildup. It is effective over a broad temperature range and results in lower power consumption under varying load conditions.*

## APPLICATIONS

- High Temperature Process Ovens
- Drying Operations
- Can and Fiber Board Lines
- Glass Fiber Ovens
- Extrusion Paint Lines
- Multi-Purpose E.P. Gears
- Tenter Frames
- Open Bearings and many other Roller Chain Operations requiring a lubricant with excellent heat stability

## CHARACTERISTICS

## PERFORMANCE

### Physical Properties

Viscosity Grade	150
Viscosity	
@ 100°F,	cSt 154.8
@ 210°F,	cSt 19.05
@ 100°F,	SUS 717
@ 210°F,	SUS 94.48
Viscosity Index	150
Pour Point, °F (°C)	-60 (-51)
Flash Point, °F (°C)	575 (302)
Specific Gravity	0.911
Density, lbs/gal	7.59

For additional product information contact your local distributor representative or email us at [Info@santexdirect.com](mailto:Info@santexdirect.com)