



NATURAL GAS COMPRESSOR OIL

PRODUCT INFORMATION

Santex SNGP Series lubricants are synthetic blends formulated from highly refined hydrogenated paraffinic petroleum and high temperature synthetic base stocks. The addition of **SYNTHOLATE** inhibits the formation of varnish and carbon and provides superior thermal and oxidative stability. Utilizing the superior base stocks fortified with **SYNTHOLATE** extends the life of **Santex SNGP Series** lubricants compared to that of conventional mineral oils

BENEFITS

- Reduces lubricant consumption - Extended drain intervals and lower vapor pressures reduce lubricant consumption.
- Reduces maintenance - **SYNTHOLATE** reduces carbon and varnish formation thus extending the time interval between overhauls.
- Excellent lubricity - Provides improved wear protection for bearings and other moving parts.
- Good compatibility - The base stocks and special additive package provide excellent compatibility with system components and inhibit against hydrogen sulfide corrosion.
- Improves safety - Higher flash points provide a greater margin of safety inspection results.

SNGP SERIES

PRODUCT	SNGP-32	SNGP-68	SNGP-100	SNGP-150
ISO Viscosity Grade	32	68	100	150
Viscosity				
@ 40°C, cSt	32	67	95	150
@ 100°C, cSt	5.4	10	13.1	18.6
@ 100°F, SUS	165	343	488	774
@ 210°F, SUS	44	61	72	95
Viscosity Index	103	137	136	140
Pour Point, °F (°C)	-27(-33)	-27(-33)	-25 (-32)	-25 (-32)
Flash Point, °F (°C)	440 (227)	470 (243)	440 (227)	435 (224)
Specific Gravity	0.878	0.870	0.872	0.876
Density				
@ 60°F, g/mL	0.869	0.868	0.871	0.875
@ 185°F, g/mL	0.824	0.824	0.827	0.831
Four Ball Wear Test	0.60	0.51	0.72	0.58

For additional product information contact your local distributor representative or email us at Info@santexdirect.com