



# SANTEX REFRIGERATION OIL

**Santex Refrigeration Oil Series (SPGI)** synthetic lubricants were designed for use in the compression of propane in refrigeration or unloading service. Available in three grades for rotary screw and reciprocating compressors, SPGI is especially suitable for wet gas situations. Due to the varying make-up of gases and operating temperatures, please contact your Santex representative for specific product recommendations.

POLYGLYCOL INSOLUBLE

<b>Physical Properties</b>			
<b>CHARACTERISTICS</b>	<b>PERFORMANCE</b>		
<b>PRODUCT</b>	<b>SPGI 68</b>	<b>SPGI 100</b>	<b>SPGI 150</b>
ISO Viscosity	68	100	150
Specific Gravity, 60°F			
Viscosity @ 40°C, cSt	69	102	156
Viscosity @100°C, cSt	12.7	18.0	26.2
Viscosity @ 100°F, SUS	349	519	788
Viscosity @ 210°F, SUS	70.2	92.2	128.1
Viscosity Index	186	195	205
Flash Point, °F (°C)	480 (249)	485 (252)	495 (257)
Pour Point, °F (°C)	-54 (-48)	-49 (-45)	-44 (-42)

For additional product information contact your local distributor representative or email us at [Info@santexdirect.com](mailto:Info@santexdirect.com)