



SANTEX REFRIGERATION COMPRESSOR OIL

Santex Refrigeration Compressor Oils (SR Series) synthetic hydrocarbon refrigeration lubricants are designed to function under severe service conditions. These fluids have a very high viscosity index, contain no paraffin and are compatible with various fluorinated refrigerants, ammonia, methyl chloride and carbon dioxide.

The **SR Series** is completely miscible with petroleum-based fluids. These fully synthetic lubricants are NSF Registered and meet USDA 1998 (H-1) guidelines (lubricants with incidental food contact). Santex R Series lubricants are Kosher Approved.

Physical Properties

CHARACTERISTICS

PERFORMANCE

PRODUCT	SR-100	SR-150	SR-200	SR-300
ISO Viscosity Grade	32	46	68	100
Specific Gravity, 60°F	0.8274	0.8323	0.8357	0.8386
Viscosity @ 40°C, cSt	31.0	45.8	63.3	95
Viscosity @100°C, cSt	5.9	7.80	10.0	13.9
Viscosity Index	135	136	143	149
Flash Point, °F (°C)	485 (252)	510 (266)	525 (274)	540 (282)
Fire Point, °F (°C)	520 (271)	530 (277)	540 (282)	555 (291)
Pour Point, °F (°C)	-87 (-66)	-65 (-54)	-65 (-54)	-60 (-51)
NSF Registered	H1	H1	H1	H1
ISO 21469	Yes	Yes	Yes	Yes
Kosher	Yes	Yes	Yes	Yes
Halal	Yes	Yes	Yes	Yes
CFIA	Pending	Pending	Pending	Pending

For additional product information contact your local distributor representative or email us at Info@santexdirect.com