



SANTEX AIR COMPRESSOR OIL

Santex Air Compressor Oil (Santex 200 Series) is formulated to provide superior lubrication performance in air compressors operating at temperatures below 200°F. This lubricant was specifically designed to provide extended service to rotary-screw air compressors operating within normal conditions. The 200 Series is rated to provide superior service for 8,000 hours in most air compressor applications. Produced from the highest grade additives and base stocks available, 200 Series will continue to protect air compressors from wear and deposit formation where other compressor lubricants fail. Based on lubrication technology with millions of hours of proven performance. Santex 200 Series is compatible with most rotary screw air compressor lubricants on the market. It is not compatible with silicone or polyglycol based air compressor lubricants.

For applications where air compressor temperatures exceed 200°F, please consult your Santex sales representative about SSH and HP. Santex Industrial Products offers a lubrication solution for every air compressor application in the market.

Physical Properties

	32	46	68
ISO Viscosity Grade	32	46	68
Specific Gravity, 60°F	0.8671	0.8717	0.8747
Viscosity @ 40°C, cSt	33.8	46.4	67.5
Viscosity @100°C, cSt	6.12	7.48	9.70
Flash Point, °F	455	475	510
Fire Point, °F	475	505	540
Pour Point, °C	-51	-48	-45

For additional product information contact your local distributor representative or email us at Info@santexdirect.com