



# SANTEX AIRLINE & AIR TOOL OIL

## PRODUCT INFORMATION

Santex Airline & Air Tool Oil lubricants are high-quality lubricants specially formulated for the most demanding air tool applications. There are two grades, ISO 32 and ISO 68, to handle both small and large heavy-duty applications.

## BENEFITS

Santex Airline & Air Tool lubricants are a special blend of hydrogenated paraffin base stocks with very low pour points. Special additives have been blended with the base stock to enhance its physical properties and provide the following benefits:

- Emulsification of the moisture in the compressed air to prevent rust.
- Tough extreme pressure properties to protect tools from seizure and wear and provide good adherence to wet working surfaces.
- Resistance to oxidation to prevent lost time due to gumming & varnishing.
- Proper atomization for good lubrication and optimum control of fogging.

## APPLICATIONS

- ISO 32 is for small drills, grinders, vibrators, wrenches, screwdrivers, air nailers and staplers, air cylinders, motors, valves and chucks.
- ISO 68 is for large drills, grinders, vibrators, hand-held tools and jack hammers.

## AIR LINE & AIR TOOL OIL

### Physical Properties

ISO	32	68
Viscosity		
@ 40°C, cSt	31.93	69.40
@ 100°C, cSt	5.37	8.88
@ 100°F, SUS	165	359
@ 210°F, SUS	44.3	56.2
Viscosity Index	101	101
Pour Point, °F (°C)	-5 (-21)	0 (-18)
Flash Point, °F (°C)	430 (221)	430 (221)
Four Ball Wear Test,	0.70mm	0.65mm

For additional product information contact your local distributor representative or email us at [Info@santexdirect.com](mailto:Info@santexdirect.com)