



SANTEX AIRLINE & AIR TOOL FOOD GRADE -22 LUBRICANT

Santex Airline & Air Tool Food Grade-22 lubricant is formulated specifically for pneumatic tools used in the food service, beverage, and packaging industries. This lubricant is NSF Registered and meets U.S.D.A. 1998 (H1) guidelines (lubricants with possible incidental food contact).

Santex Airline & Air Tool Food Grade-22 is fortified with a special additive package which gives it excellent oxidation stability and low temperature fluidity. It also contains an emulsifier for superior performance in high moisture environments

Physical Properties	
CHARACTERISTICS	PERFORMANCE
PRODUCT	FOOD GRADE-22
ISO Viscosity	ISO 22
Specific Gravity, 60°F	0.860
Viscosity @ 40°C, cSt	22.3
Viscosity @100°C, cSt	4.30
Viscosity Index	96
Flash Point, °F (°C)	5 (-15)
Fire Point, °F (°C)	405 (207)
Pour Point, °F (°C)	440 (227)
Four Ball Wear Test	0.54mm
Foaming:Seq. I, II, III	0/0
Copper Strip Corrosion	1A
Rust	Pass
NSF Registered	H1

For additional product information contact your local distributor representative or email us at Info@santexdirect.com