



SANTEX POWER BLEND FOOD GRADE

Santex Power Blend FG Series hydraulic oils are formulated specially for hydraulic systems operating in the food service, beverage, and packaging industry. These synthetic blend lubricants are NSF Registered and meet USDA 1998 (H-1) guidelines (lubricants with incidental food contact). **Power Blend FG Series** lubricants are Kosher certified and CFIA accepted. Summit is an ISO 21469 certified facility.

Power Blend FG Series lubricants are fortified with oxidation inhibitors, corrosion inhibitors, as well as anti-wear additives to enhance the superior qualities offered by the Food Grade base stock. They are extended life lubricants and have the same excellent compatibility as the Santex Power Blend Series hydraulic oils.

Physical Properties

	<u>22</u>	<u>32</u>	<u>46</u>	<u>68</u>	<u>100</u>
ISO Viscosity Grade	22	32	46	68	100
Specific Gravity, 60°F	0.860	0.865	0.868	0.870	0.873
Viscosity @ 40°C, cSt	22.3	32.0	42	68	97.2
Viscosity @100°C, cSt	4.30	5.38	6.41	8.76	11.14
Viscosity Index	96	101	101	101	100
Flash Point, °C	207	230	230	232	230
Fire Point, °C	227	246	246	249	246
Pour Point, °C	-15	-15	-15	-15	-21

For additional product information contact your local distributor representative or email us at Info@santexdirect.com